

Akromatic 1250 Electric Master Stream Nozzle

STYLE 5177

The Akromatic 1250 electric master stream nozzle is designed for flows from 250 to 1250 gpm (950-4800 lpm) that have an 80 psi (5.5 bar) operating pressure. With this nozzle, you can take advantage of features including manual override, electric pattern control, pyrolite construction, and more. If you're interested in learning more about master stream nozzles like this one, find an Akron Brass distributor near you today.

Features

- Designed for flows from 250 to 1250 gpm (950-4800 lpm)
- At 80 psi (5.5 bar) operating pressure
 - Manual override
 - Pyrolite
 - Electric Pattern Control
 - 250-1250 gpm (950-4800 lpm) flow - 250-1000 gpm (950-3800) optional flow
 - 2 1/2" or 3 1/2" (65 or 89 mm) Inlet
 - No teeth
 - 12 or 24 Volt
 - 10 3/8" (264 mm) long
 - 13 lbs (5.9 kg)



Specifications

Style	5177
Certification(s)	
Warranty	
Weight	13 lbs (5.9 kg)
Type	Master Stream
Material	Pyrolite
Brand	Akromatic
Length	10 3/8" (264 mm)
Width	10 " (254 mm)
Height	8 3/4" (223 mm)

Akromatic 1250 Electric Master Stream Nozzle

STYLE 5177

Akromatic 1250 Master Stream Nozzle Specifications

Combination fog and straight stream master stream nozzle with automatic flow mechanism that provides a flow range of either 250 to 1000 gpm or 250 to 1250 gpm at 80 psi. The nozzle shall be constructed of durable, lightweight Pyrolite.