

BAND-IT

THE ULTIMATE FASTENING SYSTEMS

TIE-LOK[®] TIES

Offering a unique dimple lock with a smooth ID and a low profile, Tie-Lok[®] ties provide fast, consistent and reliable clamping tension. Used in many industries and applications, such as automotive, cable bundling and identification.



- Strong patented dimple lock
- Locks under full tension – no slipback
- Available in type 304 and type 316 Stainless Steel
- 304 provides good resistance to mild atmospheres, fresh water, UV rays
- 316 Stainless Steel for enhanced corrosion resistance in extreme environments
- Various sizes designed for standard and custom applications
- Forms a low profile single wrapped assembly to secure cables, hoses, ID Tags, CV Boots, and filter bags

PRODUCT SPECIFICATIONS

PART NO.	MATERIAL	WIDTH (IN)	LENGTH (IN)	THICKNESS (IN)	MAXIMUM DIAMETER SINGLE WRAP (IN)	MINIMUM LOOP TENSILE STRENGTH (LBS)	PACKAGE QUANTITY
AS2119	304 SS	1/4	10	0.015	2	250	100/Bag
AS2129	304 SS	1/4	16.5	0.015	4	250	100/Bag
AS2139	304 SS	1/4	22.5	0.015	6	250	100/Bag
AS2149	304 SS	1/4	29	0.015	8	250	100/Bag
AS2159	304 SS	1/4	35	0.015	10	250	100/Bag
AS4119	316 SS	1/4	10	0.015	2	250	100/Bag
AS4129	316 SS	1/4	16.5	0.015	4	250	100/Bag
AS4139	316 SS	1/4	22.5	0.015	6	250	100/Bag
AS4149	316 SS	1/4	29	0.015	8	250	100/Bag



