

GOFIGHTER™





Performance Data Applies to both single or multi pressure pump variants unless stated	2010*	3010*	4010	6010	
Priming Performance Range	To 7.5m	To 7.5m	To 7.5m	To 7.5m	
Priming Speed (recommended)	2500rpm	2500rpm	2500rpm	2500rpm	
Max. Suction Pressure	12 bar	12 bar	12 bar	12 bar	
Max. Recommended Speed	3600 rpm	3600 rpm	3600 rpm	3600 rpm	
Minimum idle speed	900 rpm	900 rpm	900 rpm	900 rpm	
For other applications please co	For other applications please contact IDEX India Pvt. Ltd.				
Maximum Outlet Pressure – Low Pressure (EN compliance)	17 bar	17 bar	17 bar	17 bar	
Maximum Outlet Pressure – High Pressure (EN compliance) *Multi pressure only	54.5 bar	54.5 bar	54.5 bar	54.5 bar	
Max. Flow – Low Pressure	3400 l/min	4200 l/min	6200 l/min	7750 l/min	
Max. Flow – High Pressure *Multi pressure only	770 l/min	770 l/min	770 l/min	770 l/min	
Weight (based on alum. model)	Single 85 kg	Single 92.5 kg	Single 125.5 kg	Single 125.5 kg	
Approx. Weights, will vary according to specification and gunmetal spec	Multi 105 kg	Multi 117 kg	Multi 145.5 kg	Multi 145.5 kg	
Typical Dimensions	Single	Single	Single	Single	
(Lx W x H) mm	714 x 580 x 626	772 x 764 x 661	772 x 764 x 661	772 x 764 x 661	
	Multi	Multi	Multi	Multi	
	740 x 580 x 787	806 x 770 x 790	806 x 770 x 825	806 x 770 x 825	
EN1028 Priming Times from 7.5m	22 sec (4" hose)	32 sec (5½" hose)	32 sec (5½" hose)	68 sec (8" hose)	
Thermal Relief	42°C	42°C	42°C	42°C	

III certified

Basis of Data: F1/F2. 2010 with Piston Primer, 2 UK Delivery Valves, 4" RT suction. 3010/4010/6010 with Piston Primer, 4 UK Delivery Valves. 3010/4010. 5 ½" RT Suction, 6010 8" suction. Mounted on standard platform. Water ring primer option also available.

F1/F2_2010	F1/F2_3010	F1/F2_4010	F1/F2_6010		
2000 L/min	3000 L/min	4000 L/min	6000 L/min		
At 10 bar	At 10 bar	At 10 bar	At 10 bar		
3m lift	3m lift	3m lift	3m lift		
F2 only - High pressure rating 250 L/min at 40 bar					

IDEX India Pvt. Ltd.
Survey. No. 256, GIDC Manjusar,
Savli, Nr. Bombardier Circle.
Dist. :Vadodara- 391 770
Gujarat, India - Tel +91-2667 662559



Contact us:

info.fmt@idexcorp.com Toll Free: 1800 267 9955 www.idexindia.in

Reliable Sturdy Robust **Vehicle Mounted Pumps**



FEATURES

- Compact, powerful and versatile
- Most efficient Pump in its category offering a range of flows
- Single and multi pressure pump for rear mounting
- Ready to use mounting platform for ease of installation
- Available in Aluminium or Gunmetal MOC
- GODIVA reliability and trust





LOCAL CAPABILITY

- World class product manufactured locally
- State of the Art
 manufacturing facility with
 SCADA based PLC control
 and testing lab
- Faster service & support
- Experienced staff trained at GODIVA UK
- Local inventory of genuine spares
- Refurbishment & extended warranty